



OFFICIAL LISTING

NSF certifies that the products appearing on this Listing conform to the requirements of
NSF/ANSI 169 - Special Purpose Food Equipment and Devices

This is the Official Listing recorded on July 20, 2026.

Aignep S.P.A.
Via Don G. Bazzoli, 34
25070 Bione (BS)
Italy
39 03 658 96626

Facility: Bione (BS), Italy

Fittings - 53000 Series^[1] [Pb]

53020 (1) (2)	53040 (1)(2)	53040X (1)(2)	53116 (1)(2)	53116X (1)(2)
53117 (1)(2)	53117X (1)(2)	53130 (1)(2)	53130X (1)(2)	53140 (1) (2)
53140X (1) (2)	53216 (1)(2)	53216X (1)(2)	53217 (1) (2)	53217X (1) (2)
53230 (1)(2)	53230X (1)(2)	53240 (1) (2)	53240X (1) (2)	

Fittings - 54000 Series^[1] [Pb]

54020 (1) (2)	54040 (1) (2)	54050 (1) (2)	54116 (1) (2)	54130 (1) (2)
54140 (1) (2)	54216 (1) (2)	54230 (1) (2)	54600 (1) (2)	54610 (1) (2)
54625 (1) (2)				

Fittings - 60000 Series^[1] [6] [Pb]

60000(1)(2)	60005(1)(2)	60006(1)(2)	60015(1)(2)	60020(1)(2)
60030(1)(2)	60040(1)(2)	60050(1)(2)	60106(1)(2)	60106X(1)(2)
60110(1)(2)	60110X(1)(2)	60111(1)(2)	60111X(1)(2)	60115(1)(2)
60115X(1)(2)	60116(1)(2)	60130(1)(2)	60130X(1)(2)	60210(1)(2)
60210X(1)(2)	60211(1)(2)	60211X(1)(2)	60215(1)(2)	60215X(1)(2)
60216(1)(2)	60230(1)(2)	60230X(1)(2)	60310X(1)(2)	60600(1)(2)
60700(1)(2)	60820(1)(2)	61005(1)(2)	61020(1)(2)	61040(1)(2)
61050(1)(2)	61100(1)(2)	61115(1)(2)	61130(1)(2)	61200(1)(2)
61220(1)(2)	61230(1)(2)	61700(1)(2)	62000(1)(2)	62005(1)(2)
62020(1)(2)	62040(1)(2)	62080(1)(2)	62092(1)(2)	62300(1)(2)
62310(1)(2)	62315(1)(2)	62320(1)(2)	62340(1)(2)	62355(1)(2)
62400(1)(2)	62420(1)(2)	62430(1)(2)	62440(1)(2)	62450(1)(2)
62500(1)(2)	62510(1)(2)	62520(1)(2)	62600(1)(2)	62610(1)(2)
63220(1)(2)	66300(1)(2)	66310(1)(2)	66560(1)(2)	66570(1)(2)
69200(1)(2)	69220(1)(2)	69260(1)(2)	69280(1)(2)	69460(1)(2)
69480(1)(2)	69485(1)(2)	69680(1)(2)	69740(1)(2)	FE004(1)(2)

Fittings - Brass 59000 Range^[1] [Pb]

59005(1)(2)	59020(1)(2)	59030(1)(2)	59040(1)(2)	59100(1)(2)
59111(1)(2)	59116(1)(2)	59130(1)(2)	59211(1)(2)	59216(1)(2)
59223(1)(2)	59226(1)(2)	59230(1)(2)		

Fittings 70000 Series^[2] [3] [Pb]

70000 (1)(2)	70010 (1)(2)	70020 (1)(2)	70030 (1)(2)	70040 (1)(2)
70050 (1)(2)	70100 (1)(2)	70106 (1)(2)	70116 (1)(2)	70126 (1)(2)

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF.



70130 (1)(2)	70200 (1)(2)	70216 (1)(2)	70226 (1)(2)	70230 (1)(2)
70310 (1)(2)	70500 (1)(2)	70505 (1)(2)	70510 (1)(2)	70550 (1)(2)
70560 (1)(2)	70600 (1)(2)	70610 (1)(2)	70625 (1)(2)	70700 (1)(2)
71000 (1)(2)	71010 (1)(2)	71015 (1)(2)	71020 (1)(2)	71021 (1)(2)
71030 (1)(2)	71040 (1)(2)	71050 (1)(2)	71100 (1)(2)	71101 (1)(2)
71110 (1)(2)	71115 (1)(2)	71120 (1)(2)	71130 (1)(2)	71200 (1)(2)
71210 (1)(2)	71215 (1)(2)	71220 (1)(2)	71230 (1)(2)	71300 (1)(2)
71410 (1)(2)	71420 (1)(2)	71430 (1)(2)	71500 (1)(2)	71510 (1)(2)
71700 (5)(6)FG	71703 (5)(6)FG	LG71410 (3)(4)	LG71500 (3)(4)	

Solenoid Valves - Fluidity^[4] [Pb]

F1D (1)(2)(3)(4)(5)	F1F (1)(2)(3)(4)(5) ^[4]
F2D (1)(2)(3)(4)(5)	F2F (1)(2)(3)(4)(5) ^[4]
F4D (1)(2)(3)(4)(5)	F4F (1)(2)(3)(4)(5) ^[4]
X1D (1)(2)(3)(4)(5)	X1F (1)(2)(3)(4)(5) ^[4]
X2D (1)(2)(3)(4)(5)	X2F (1)(2)(3)(4)(5) ^[4]
X4D (1)(2)(3)(4)(5)	X4F (1)(2)(3)(4)(5) ^[4]

[1] (1) 2 digits indicating seal variant
(2) 3 digits indicating size

[2] (1) 2 digits indicating seal variant
(2) 3 digits indicating size
(3) 1 digit indicating seal variant
(4) 2 digits indicating size
(5) 3 digits indicating special variant
(6) 3 digits indicating size

[3] Certified for use as part of a food equipment item with a resulting overall weighted average lead content of = 0.25% in the water contact portion of the equipment.

[4] (1) Port size options:
03 - 1/4"
04 - 3/8"
05 - 1/2"
07 - 3/4"
09 - 1"
XF - 1 1/4"
XG - 1 1/2"
XH - 2"
J4 - 25x25mm
(2) Functions options:
1 - 2/2NC (normally closed)
2 - 2/2NO (normally open)
3 - 3/2"NC (normally closed)
4 - 3/2"NO (normally open)
B - 2/2 (latching)
(3) Dn(mm) options: 15,02,03,04,10,14,18,25,40,50.
(4) Sealing material options:
N - NBR
E - EPDM
V - FKM
(5) Thread version options:
blank -Gas
N - NPTF
0 - Standard

[5] The contact with the food is limited to potable, non-carbonated water under constant service pressure.

[6] Only acceptable for use in contact with coffee, tea, and potable water.

[Pb] Product also evaluated and determined to possess weighted average lead content of <=0.25% and complies with lead content requirements for "lead free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF.